


TLE20001B



※only with TLE03501B

FEATURES

- The shape is unified with GE series of the same series.
- Beautiful appearance, generous.
- Beautiful shape, noble quality.
- It is easy to install and use.
- The unique bubble spitting technology makes the water flow smooth and strong.
- 1.3L water can save water and bring more comfortable experience.

SPECIFIECS

- Water Inlet Requirement : 0.05MPa(Dynamic Pressure) ~0.75MPa(Static Pressure)
- Water Efficiency : Grade1
- Drainage accessory : not included
- Operating temperature : 1~55°C
- Detection range: ≤250mm

OTHERS

- Product series: GE Series
- Recommend fittings :
- Functional Part: TLE01501B(AC) TLE04501B(DC) TLE03501B(HYDRO ELECTRIC POWER)
- Thermostatic : TLE05701B

TLE20001B+TLE01501B/TLE03501B/TLE04501B Aqua-auto faucet(single)



TOTO(CHINA) CO.,LTD. All rights reserved.

TLE20001B+TLE01501B/TLE03501B/TLE04501B +TLE05701B Aqua-auto faucet(thermal)



TOTO(CHINA) CO.,LTD. All rights reserved.

TOTO(CHINA) CO.,LTD. www.toto.com.cn